



HARMONIC EU CAVITY COMISSIONING: OPERATION AND TBL COMPENSATION

HarmonLIP 2025 - Cerdanyola del Vallès, Spain

24/10/2025

Hamed Shaker on behalf of 3HC Collaboration



HZB Helmholtz
Zentrum Berlin



ALBA 3HC at BESSY-II

Table 1: Harmonic EU cavity parameters

Parameter	Value	Unit
Maximum voltage	200	kV
Shunt impedance	1.1	M Ω
Unloaded quality factor Q_0	14000	-
Tuning range	12.4	MHz

Main cavity parameters measured at the central resonance frequency, f_0 .

Parameter	Symbol	Value	Unit
Reflection coefficient	S_{11}	-50.8	dB
Coupling factor	β	1.006	-
Bandwidth	BW	214	kHz
Loaded quality factor	Q_l	6995	-
Unloaded quality factor	Q_0	14 031	-
Transmission to pick-up antenna	S_{21}	-45.9	dB

Input data used to calculate the impedance budgets of BESSY II.

Parameter	Symbol	Value	Unit
Revolution frequency	f_{rev}	1.2492	MHz
Beam current	I_b	300	mA
Beam energy	E	1.7	GeV
Momentum compaction factor	α	$7.3 \cdot 10^{-4}$	-
Synchrotron frequency	f_s	$7.0 \cdot 10^3$	Hz
Beta function	β	5.0	m
Longitudinal damping decrement	τ_s	752	s ⁻¹
Transversal damping decrement	$\tau_{x,y}$	250	s ⁻¹

Active harmonic EU cavity: Commissioning and operation with beam, F. Perez et al., Nuclear Instruments and Methods in Physics Research A 1072 (2025) 170195
And Summary of the commissioning of the active harmonic EU cavity, F. Perez et al., IPAC24, US



3HC collaboration



A collaboration between ALBA, HZB and DESY. ALBA 3HC cavity and LLRF installed in BESSY-II since 2022 and dismantled on August 2025.

Some recent achievements:



- TBL compensation
- Near flat potential operation
- Passive loop operation

TRANSIENT BEAM LOADING (TBL)



- In RF cavities, the **beam induced voltage** (the beam loading), V_b represents a considerable part of the total voltage, V_c . This contribution can be around the 40% in the MC and $> 80\%$ in the HC
- V_b is built on the **successive passage** of bunches. It reaches an **equilibrium** when the decay of the cavity voltage between bunch passages matches the voltage added by each bunch

$$V_b = - \left(\frac{1}{2} V_{b0} + V_{b1} e^{-\frac{t_1}{\tau_f}} e^{i\psi_1} + V_{b2} e^{-\frac{t_2}{\tau_f}} e^{i\psi_2} + \dots \right) = -\frac{1}{2} V_{b0} - \sum_{l=1}^N V_{b0} e^{l(-\delta + i\psi)}$$

- Uneven charge distribution** in the buckets, such as gaps, break the homogeneous build-up causing a periodic modulation in the cavity voltage with a period equal to the revolution time



TRANSIENT BEAM LOADING (TBL)



- The **different MC and HC voltages** seen by the bunches cause different bunch properties (synchrotron frequency, bunch length, phase, etc.) along the bunch train
- The bunch length, and thus the **Touschek beam lifetime**, is **specially affected** in the case of a double NC RF system tuned to maximize them
- Just a 2% gap can lead to Touschek lifetime reductions of about 45%
- Transient beam loading (TBL) **compensation** is therefore highly recommended in case a gap in the beam is foreseen

TBL COMPENSATION - METHODOLOGY

- Taking advantage of the active HCs, it is possible to modulate the generator induced voltage V_b , to **counter** the modulation induced by the beam and get a flatter cavity voltage (V_c) :

$$V_c(t) - V_b(t) = V_g(t)$$


which gives us **the ideal V_g** to fully compensate the TBL. From this signal, I_g and then P_g can be then calculated [1]:

$$I_g(t) = \frac{1}{k} \left[\frac{dV_g(t)}{dt} + \frac{1}{\tau_f} [1 - i \tan \psi_d] V_g(t) \right] \quad \longrightarrow \quad P_g(t) = \frac{R_s |I_g(t)|^2}{8\beta}$$

- However, RF cavities have a **narrow bandwidth** and **do not accept well** the high frequency **components** of the modulated power required to fully compensate the TBL. A very **high generator** power is required for some buckets, far exceeding the available one, resulting in a high reflected power, as well
- Following the strategy proposed by [1], we **can filter out most of the high frequency components** to effectively mitigate the TBL effects with reasonable amounts of additional generator power

1. Yamamoto et al., [DOI: 10.1103/PhysRevAccelBeams.21.012001](https://doi.org/10.1103/PhysRevAccelBeams.21.012001)



TBL COMPENSATION - METHODOLOGY



- After removing the **frequency components** higher than $\pm n f_c$, where $f_c = f_{rev}$ (1.12 MHz for ALBA and ALBA II) we construct a new, filtered V_g :



$$V_g(t) = e^{\alpha(t-t_0)} \left[V_g(t_0) + k \int_{t_0}^t I_{g \text{ filt}}(t') e^{-\alpha(t'-t_0)} dt' \right]$$

- The result is a **flatter cavity voltage signal**, both in amplitude and phase, for both the MCs and HCs, without requiring so much power:




TBL COMPENSATION - METHODOLOGY

- For the ALBA II baseline scenario, for instance, full compensation in the HCs would require **80 kW of power**
- By filtering the harmonics higher than $1 f_{rev}$, the required power is only 1 kW above the no-gap case, reaching a maximum of **5.4 kW**
- With the proposed compensation scheme, the average **power consumption** remains approximately **the same** as without compensation





TBL COMPENSATION - ALBA II CASE

- Even if **just a 2% of gap** has a **heavy impact** on the average bunch length, further increasing it does not seem to worsen it much
- For **gaps < 2%**, compensations higher than 97% should be **easily achieved**
- **Tracking** simulations for the **compensation** case are in progress




TBL COMPENSATION - ALBA II CASE

- In the ALBA II baseline scenario (with only a 1.8% gap), correcting only the 1st revolution harmonic would yield a **very high compensation efficiency**, with an average bunch length of 30.92 ps, around 98% of the no-gap case, 31.6 ps.




TBL COMPENSATION - ALBA II CASE

- The bunch **form factor** and **bunch phase** have been included in the TBL calculation. Convergence is achieved after approximately 10-15 iterations
- **Tracking simulations** have been performed with elegant to cross-check the semi-analytical results, showing **good agreement** between both approaches within the linear region




TBL COMPENSATION - ALBA II CASE

- Even if **just a 2% of gap** has a **heavy impact** on the average bunch length, further increasing it does not seem to worsen it much
- For **gaps < 2%**, compensations higher than 97% should be **easily achieved**
- **Tracking** simulations for the **compensation** case are in progress



Implementation on the LLRF system


- Implemented a new control module includes IIR bandpass-filter and positive/negative frequency separator modules.
- Feedforward/feedback drive allows to send revolution harmonic content to cavities.
- Source can be chosen between:
 - External reference (Feedforward)
 - Cavity voltage: Mode +-1 (Feedback)




S. Shaker et al., "Development of a 500 MHz direct RF sampling low-level RF system for ALBA and ALBA-II", in Proc. IPAC'25, Taipei, Taiwan

Harmonic feedback diagram


TBL Compensation: Setup



External reference
experimental setup




External reference harmonic content




Forward and reflected power
with and w/o compensation measurements

- Compensation applied during 3HC commissioning in BESSY II.
- Current: 300 mA, Main RF Voltage: 0.7 MV (2 cavities parked, 2 with detuning -25 deg.), Landau cavities: parked, **Fill pattern: 25% gap**, 3HC: 130 kV (detuning 0 deg).
- External reference built with analogue mixer and filtered using digital harmonic resonant feedback.

TBL Compensation – Harmonic Reduction




Cavity harmonic content w/o compensation




Cavity harmonic content with compensation

- Compensation applied during 3HC commissioning in BESSY II.
- Current: 300 mA, Main RF Voltage: 0.7 MV (2 cavities parked, 2 with detuning -25 deg.), Landau cavities: parked, Fill pattern: 25% gap, 3HC: 130 kV (detuning 0 deg).
- Harmonic content of the cavity **is reduced by ~ -30 dB**.

TBL Compensation : Result



**Avalanche Photo Diode arrival time
with and w/o compensation measurements**




**Bunch phase arrival time
with and w/o compensation simulation**

- Compensation applied during 3HC commissioning in BESSY II.
- Current: 300 mA, Main RF Voltage: 0.7 MV (2 cavities parked, 2 with detuning -25 deg.), Landau cavities: parked, Fill pattern: 25% gap, 3HC: 130 kV (detuning 0 deg).
- TBL compensated from 114 ps to 102 ps: **-10,5 %**.

TBL Compensation : Analysis

Phase transient for different generator current in 1st revolution harmonic







ALBA 3hc	Reference	Full compensation	Minimal phase transient
Generator current on 1st rev. harmonic, (A)	0	0.0702+0.0039j	0.250-0.034j
Phase transient (max-min, ps)	72.89	56.99	18.97

- model reproduces the numbers for reference case (blue) and for the case of compensated 1st harmonic (red)
- Transient for the case of compensated 1st harmonic is achieved at generator current $I_{\text{gen}} = -(-0.070 - 0.0039j)$
- minimal phase transient amplitude is predicted for $I_{\text{gen}} = -(-0.250 + 0.034j)$ (green)
- This last case was not observed

Flat Potential Operation

300mA homogeneous filling pattern beam
close to flat longitudinal potential at BESSY II



30-bunches gap, 1.0MV main RF
Harmonic cavities parked


Flat Potential Operation - Steps

	Main RF	Passive 3hc	Active 3hc	Fill pattern	Current achieved	transient / bunch length (FWHM)	Life time	Comments
1	1400kV (4x350kV)	4x3kW (=270kV), lengthening (I)	120kV	Gap 100 bunches	300mA	250ps/ ?	5.9H	We already new it is a stable state, however lifetime improvement is small due to the transient
2	1400kV	4x3kW, (I)	70kV, 120kV	Homogeneous	250mA	~15ps/ ?	11.9H	4 tries with beam losses at current from 254mA to 267mA Increasing active 3hc amplitude does not make it better...
3	1400kV	Park-lengthening (+0.5 F_rev)	70kV, 120kV	Homogeneous	242mA, 211mA			Reduced threshold advises it could be mode 1 coupled bunch instability. To stabilize it additional impedance at -1 revolution harmonic would help -> park something there!
4	1400kV	4x3kW, (I)	parked (-0.5 F_rev)	Homogeneous	300mA		8.9H	It works! Stable for 40 min during lunch break. -> Reduce main RF.
5	950kV	4x3kW, (I)	parked (-0.5 F_rev)	Homogeneous	300mA		12.5H	Unstable at lower main RF amplitudes, but it is a different kind of instability, the beam does not get lost. -> Park a passive 3hc at ~-0.6 F_rev and activate ALBA 3hc.
6	1400kV	3x3kW, (I) LC3 at ~-0.6 F_rev	100kV	Homogeneous	300mA		9.44H	Stable! -> Reduce main RF.
7	1040kV	3x3kW, (I) LC3 at ~-0.6 F_rev	115kV	Homogeneous	300mA	~9ps/ 140ps	15.6H	Stable! Close to quartic potential!

Passive Loop Operation – 200kV & 210kV


```

Terminal - opi@opic24c /home/opic/struckcal
File Edit View Terminal Tabs Help
Every 3.0s: python3 cali... opic24c: Tue May 20 23:50:48 2025
Cavity voltage setpoint: 17.23 kV
Cavity voltage measurement: 200.14 kV
Waveguide forward power: 0.06 kW
Waveguide reverse power: 13.18 kW
Cavity input power: -13.13 kW
Cavity dissipated power: 18.21 kW
Beam power: -31.33 kW
Beam synchronous phase: -51.45 °
  
```





For the stability test over night:


- switch OFF 3hc SSA
- set water flow of the RF load after circulator to ~27 (l/min)
- set slow interlock reflected power level to 20kW (73.0 dBm)
- inject 200mA and go to passive loop on the shortening side at **200kV** (~18.3 kW cavity dissipated power)
- Long stability test for this setup - overnight.
- Maximum stable **210kV** was achieved.



Passive Loop Operation - 100 kV



Passive Loop Operation - Thermal instability



- Cavities are on thermally unstable arm in lengthening
- Picture for a passive 3hc (BESSY-II Landau cavity)
- Blue arrows - LLRF passive loop operation




www.cells.es

Cerdanyola del Vallès (Barcelona) Spain

Tel: (+34) 93 592 43 00


Passive Loop Operation



- Outliers by plunger movement or injection
- Both by plunger movement up and down

Test at BESSY-II

- Machine state: current 170mA, amplitude main RF - 1.4MV, Landau cavities – lengthening, fill pattern - 25% gap, ALBA 3hc – “parked” close to +1 rev. harmonic (plunger pos. 4.39).
- Two transients recorded on 02.07.2025 overlayed: timestamps 21:14:25 (red, without compensation) and 21:17:10 (blue, with compensation). Transient reduction according to E_log from 73ps to 57ps, or about 20%.
- The revolution signal mixed with the master Oscillator signal and fed to the LLRF system for the feed-forward system



Test at BESSY-II

- Machine state: current 300mA, main RF - 0.7MV (2 cavities parked, 2 with detuning -25 deg.), Landau cavities – parked, fill pattern - 25% gap, ALBA 3hc – at 130 kV, 0 deg.
- Two transients recorded on 02.07.2025 overlayed: timestamps 22:32:00 (red, without compensation) and 22:36:30 (blue, with compensation). Transient reduction according to E_log from 114ps to 102ps, or about 10%.

